

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A motor comprising:
a stator;
a rotor rotatably disposed around the stator; and
a rotor cup having cooling-holes formed at the bottom part thereof for allowing external air to flow into the inside of the rotor cup therethrough, and lower blades formed at the bottom part thereof for generating a blowing force, the rotor being fixed to the rotor cup at the inner circumference thereof,

wherein each of the lower blades is protruded from one side of each of the cooling-holes towards the stator, and

wherein each of the lower blades and the cooling-holes has an acute sloping angle to the line extended in the rotating direction of the rotor cup and perpendicular to the radial direction of the rotor cup.

~~wherein the lower blades and the cooling holes are formed such that each of the lower blades and the cooling holes is at a prescribed angle to the radial direction of the rotor cup.~~

2. – 4. (Canceled)

5. (Previously Presented) The motor as set forth in claim 1, wherein the rotor is provided at the upper side thereof with upper blades for supplying external air to the upper part of the rotor when the rotor is rotated.

6. (Original) The motor as set forth in claim 5, wherein the upper blades are formed such that each of the upper blades is at a prescribed angle to the radial direction of the rotor.

7. (Original) The motor as set forth in claim 6, wherein each of the upper blades has an acute sloping angle to the line extended in the rotating direction of the rotor and perpendicular to the radial direction of the rotor.

8. (Original) The motor as set forth in claim 5, wherein the rotor cup is provided at the circumference thereof with vents for allowing the air introduced into the inside of the rotor cup to be discharged therethrough.

9. (Original) The motor as set forth in claim 1, wherein the rotor cup is provided at the circumference thereof with vents for allowing the air introduced into the inside of the rotor cup to be discharged therethrough.

10. (Original) The motor as set forth in claim 9, wherein the vents are disposed below the rotor.

11. (Original) The motor as set forth in claim 9, wherein the vents are arranged in large numbers at the circumference of the rotor cup in the circumferential direction.

12. (Original) The motor as set forth in claim 9, wherein the ratio of the whole areas of the cooling-holes to the whole areas of the vents is 2:1 to 4:1.

13. - 24. (Canceled)

25. (New) The motor as set forth in claim 1, wherein the cooling-holes are rectangular in shape.

26. (New) The motor as set forth in claim 1, wherein a perimeter of each cooling-hole is located entirely within a flat bottom portion of the bottom part.

27. (New) The motor as set forth in claim 1, wherein a shape of the lower blades is the same as a shape of the cooling-holes.

28. (New) The motor as set forth in claim 1, wherein a size of the lower blades is the same as a size of the cooling-holes.

29. (New) The motor as set forth in claim 1, wherein each lower blade is a portion of the bottom part that has been cut and bent upwardly.